

# PRODUCT SPECIFICATIONS

## LPR RIDGE VENT

### 1.1 MATERIALS:

- 1.1.1 Aluminum Alloy:** Conforms to ASTM B209  
0.025" Aluminum Coiled Sheet (Embossed on painted units)
- 1.1.2 Paint:** Factory applied baked on Valspar Super Flex with minimum 0.8 top coat and minimum 0.3 wash coat.
- 1.1.3 Accessories:**  
End Plug: High-density polyethylene.

### 1.2 MISCELLANEOUS:

- 1.2.1 Description:** Roll-formed, aluminum ridge vent. Adjustable to roof pitches from 3/12 to 12/12. Features a roll-formed, one-piece construction; external weather baffle; pre-punched nail holes; and male/female ends for easy connection. May be cut at 2 foot internals. Embossed for extended paint life, durability, and blended appearance with shingles. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.
- 1.2.2 Color:** Available in BROWN, WHITE, BLACK, WEATHERED BRONZE and MILL finish.
- 1.2.3 Net Free Area:** 18 square inches per linear foot. (144 square inches per 8 foot part, 180 square inches per 10 foot part.)
- 1.2.4 Packaging:** Packaged 10 to a carton. Available in 8 and 10 foot lengths. UPC labels are affixed to each vent and carton. End plug available, sold separately.
- 1.2.5 Performance:** Passed Miami-Dade County test requirements for structural uplift and wind driven rain infiltration.
- 1.2.6 Approvals:** Miami-Dade County Approved – NOA No: 11-0602.01, expires: 08/17/16. Texas Department of Insurance "Windstorm" Approved – Product Evaluation Report No: RV-13.



P.O. Box 519  
Jacksonville, AR 72078  
1-800-643-5596 phone  
501-982-1258 fax