Issuing Date 13-Jul-2015

Revision Date 27-Oct-2015

Revision Number 3

SAFETY DATA SHEET



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE **COMPANY/UNDERTAKING**

Product identifier	
Product Name	Big Stretch
Other means of identification	
Synonyms	None
Recommended use of the chemical	and restrictions on use
Recommended Use	Caulking
Uses advised against	No information available
Details of the supplier of the safety of	data sheet
Supplier Name	Sashco, Inc.
Supplier Address	10300 E. 107th Place Brighton CO 80601 US
Supplier Phone Number	Phone:303-286-7271 Contact Phone303-286-7271
Supplier Email	stunney@sashco.com
Emergency telephone number	800-535-5053

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1B



Specific target organ toxicity (repeated exposure)

Category 2

GHS Label elements, including precautionary statements

Emergency Overview			
Signal word		Danger	
Hazard Staten	nents		
Causes serious			
May cause car			
May cause dar	nage to organs through	prolonged or repeated exposure	
!			
Appearance	Various Colors	Physical state Paste Liquid	Odor Sweet

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention.

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

<u>Unknown Toxicity</u> 88.5925% of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful if swallowed Toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.



3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Limestone	1317-65-3	10 - 30	*
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	3 - 7	*
Ethylene glycol	107-21-1	1 - 5	*
Ethylene oxide-Nonylphenol polymer	9016-45-9	1 - 5	*
Ammonium hydroxide	1336-21-6	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice	Show this safety data sheet to the doctor in attendance.		
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.		
Skin contact	Wash with soap and water.		

Inhalation Remove to fresh air.

Ingestion Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Burning sensation. Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.



5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Uniform Fire Code Irritant: Liquid

Hazardous Combustion Products Carbon oxides.

Explosion Data Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas.
Other Information	Refer to protective measures listed in Sections 7 and 8.
Environmental precautions	
Environmental precautions	Refer to protective measures listed in Sections 7 and 8.
Methods and material for containme	ent and cleaning up
Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.



7. HANDLING AND STORAGE

Precautions for safe handling

Handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact wit skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.	
Conditions for safe storage, including any incompatibilities		
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place.	
Incompatible Products	None known based on information supplied.	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Limestone	-	TWA: 15 mg/m ³	TWA: 5 mg/m ³ respirable dust
1317-65-3		TWA: 5 mg/m ³	TWA: 10 mg/m ³ total dust
		(vacated) TWA: 15 mg/m ³	
		(vacated) TWA: 5 mg/m ³	
Petroleum distillates, hydrotreated heavy	TWA: 5 mg/m ³ , as oil mist,	TWA: 5 mg/m ³ , as oil mist,	
paraffinic	mineral	mineral	
64742-54-7	STEL: TWA: 10 mg/m ³ , as oil		
	mist, mineral		
Ethylene glycol	Ceiling: 100 mg/m ³ aerosol only	(vacated) Ceiling: 50 ppm	
107-21-1		(vacated) Ceiling: 125 mg/m ³	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures	Showers Eyewash stations Ventilation systems
Individual protection measures, suc	ch as personal protective equipment
Eye/face protection	If there is a risk of contact: Wear safety glasses with side shields (or goggles). None required for consumer use.
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Appearance Color	Liquid Viscous paste Various colors
Property_	Values
рН	9.0
Melting / freezing point	No data available
Boiling point / boiling range	100 °C / 212 °F
Flash Point	>93.3 °C />200 °F
Evaporation Rate	No data available
Flammability (solid, gas)	No data available
Flammability Limit in Air	
Upper flammability limit	No data available
Lower flammability limit	No data available
Vapor pressure	No data available
Vapor density	No data available
Specific Gravity	1.1
Water Solubility	Miscible in water
Solubility in other solvents	No data available
Partition coefficient: n-octanol/wate	erNo data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available
Other Information	
Softening Point	No data available
VOC Content (%)	No data available

VOC Content (%) Particle Size Particle Size Distribution No data available No data available No data available Odor Odor Threshold Sweet No information available

Remarks Method

None known None known None known None known None known None known

None known None known None known None known None known None known None known None known

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. May cause redness, itching, and pain. May cause temporary eye irritation.

Skin contactSpecific test data for the substance or mixture is not available. May cause irritation.Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene glycol 107-21-1	= 4000 mg/kg (Rat)	-	-
Ethylene oxide-Nonylphenol polymer 9016-45-9	-	= 1780 µL/kg (Rabbit)	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-

Information on toxicological effects



Symptoms

May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.
Mutagenic Effects	No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	A2	Group 1		X
ACGIH (American Confere A2 - Suspected Human Carc IARC (International Agency Group 1 - Carcinogenic to H OSHA (Occupational Safet X - Present	cinogen y for Research on Cance umans	r)	of Labor)	
Reproductive toxicity	No informatio	No information available.		
STOT - single exposure	No informatio	No information available.		
STOT - repeated exposure	classification 1910.1200), t	May cause damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure (STOT RE).		
Chronic Toxicity		Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposu may cause chronic effects.		posure. Prolonged exposure
Target Organ Effects		Eyes. Respiratory system. Skin. Gastrointestinal tract (GI). Central Nervous System (CNS Cardiovascular system. Heart. Kidney.		tral Nervous System (CNS).
Aspiration Hazard	No informatio	No information available.		
Numerical measures of toxi	icity Product Informa	ation		

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 2,008.00 mg/kg ATEmix (dermal) 20,083,764.00

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT. The percentage of marine pollutant or severe marine pollutant is below values regulated by DOT

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7		96h LC50: > 5000 mg/L (Oncorhynchus mykiss)		48h EC50: > 1000 mg/L
Ethylene glycol 107-21-1	96h EC50: 6500 - 13000 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 41000 mg/L (Oncorhynchus mykiss) 96h LC50: 14 - 18 mL/L (Oncorhynchus mykiss) 96h LC50: = 40761 mg/L (Oncorhynchus mykiss) 96h LC50: = 27540 mg/L (Lepomis macrochirus) 96h LC50: = 16000 mg/L (Poecilia reticulata) 96h LC50: 40000 - 60000 mg/L (Pimephales promelas)	EC50 = 620.0 mg/L 30 min	48h EC50: = 46300 mg/L
Ammonium hydroxide 1336-21-6		96h LC50: = 8.2 mg/L (Pimephales promelas)		48h EC50: = 0.66 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Ethylene glycol 107-21-1	-1.93

Other adverse effects

No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 281

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ammonium hydroxide	Toxic
1336-21-6	Corrosive

14. TRANSPORT INFORMATION

DOT Proper Shipping Name Hazard Class Marine Pollutant	NOT REGULATED NON REGULATED N/A This product contains a chemical which is listed as a marine pollutant according to DOT The percentage of marine pollutant or severe marine pollutant is below values regulated by DOT
TDG	Not regulated
MEX_	Not regulated
ICAO	Not regulated
IATA Proper Shipping Name Hazard Class	Not regulated NON REGULATED N/A
IMDG/IMO Hazard Class	Not regulated N/A
RID	Not regulated
ADR	Not regulated
ADN	Not regulated



15. REGULATORY INFORMATION

International Inventories

TSCA DSL Complies All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene glycol - 107-21-1	107-21-1	1 - 5	1.0
Ammonium hydroxide - 1336-21-6	1336-21-6	0.1 - 1	1.0

SARA 311/312 Hazard Categories

Yes
Yes
No
No
No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium hydroxide 1336-21-6	1000 lb			Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylene glycol 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Ammonium hydroxide 1336-21-6	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Quartz - 14808-60-7	Carcinogen
Ethyl alcohol - 64-17-5	Carcinogen Developmental

U.S. State Right-to-Know Regulations



Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Limestone 1317-65-3	Х	Х	Х		
Ethylene glycol 107-21-1	Х	Х	Х	Х	Х
Ammonium hydroxide 1336-21-6	Х	Х	Х	Х	

International Regulations

Mexico

National occupational exposure limits

	Component		Carcinogen Status	Exposure Limits
	Limestone			Mexico: TWA= 10 mg/m ³
1	317-65-3 (10 - 30)			Mexico: STEL= 20 mg/m ³
	Ethylene glycol			Mexico: Ceiling 100 mg/m ³
	107-21-1(1-5)			
Maxing Occupation	nol Exposuro Limito	Caroinagana		

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

D2A - Very toxic materials D2B - Toxic materials



16. OTHER INFORMATION

NFPA HMIS	Health Hazards 1 Flammability (Physical and Chemical Hazards - Personal Protection					
Chronic Hazard Star Legend * = Chronic Health Hazard								
Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501							
Revision Date Revision Note	27-Oct-2015 No information available							

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

