



NEMEON, Incorporated
6043 Hudson Road Suite 350
Woodbury, MN 55125
www.nemeon.com

TECHNICAL DATA SHEET

SALES NUMBER: LionGUARD Black Lap Caulk LG-LC40

DESCRIPTION: Lap Caulk is a solvent-based lap caulk designed to seal and protect exposed edges of EPDM membrane lap splices.

COLOR: Black

VISCOSITY (cps): 40# .104= 40-45 sec. Seivers Rheometer

DENSITY (#/GAL.): 9.05#

% SOLIDS: 63.14

FLASH POINT (F): 79F TCC

BASE: Synthetic elastomers, resin(s) and filler(s)

SOLVENT SYSTEM: Aromatic

CLEAN-UP SOLVENT: Toluene

STORAGE: May be stored outside if covered to exclude water.

HAZARDS: Flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well-ventilated areas away from heat, sparks, fire flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS.

FREIGHT CLASSIFICATION: UN1133, ADHESIVES, 3, PGII NMFC# 170060 CLASS 55

PACKAGING: 5 gallon pails, 10.5 oz. fiber caulk tubes (25 tbs/crtn and 10 tbs/crtn)