



NEMEON, Incorporated  
6043 Hudson Road Suite 350  
Woodbury, MN 55125  
[www.nemeon.com](http://www.nemeon.com)

## TECHNICAL DATA SHEET

**SALES NUMBER:** LionGUARD Tape Primer **LG-TP70**

**DESCRIPTION:** Tape Primer is designed for use with EPDM and TPO rubber roofing installations to enhance the performance and bond of EPDM and TPO seam tape. The use of Toluene Splice Wash prior to application of this product is recommended. This product should be scrubbed into the EPDM surface thoroughly to remove surface debris. Change applicator pads frequently and cover an area in excess of the area to be seamed. When used with **clean TPO** this Primer is a Cleaner and Primer and the use of Toluene Splice Wash is not required

**COLOR:** Clear to neutral

**VISCOSITY (cps):** #3 @ 20 rpm=200 cps or less

**DENSITY (#/GAL.):** 7.22#

**% SOLIDS:** 4.8

**FLASH POINT (F):** -25F TCC

**BASE:** Synthetic elastomers, resin(s) and filler(s)

**SOLVENT SYSTEM:** Aromatics and aliphatics

**CLEAN-UP SOLVENT:** Mineral spirits, VMP Naptha or toluene

**STORAGE:** May be stored outside if covered to exclude water.

**HAZARDS:** Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well-ventilated areas away from heat, sparks, fire, flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS.

**FREIGHT CLASSIFICATION:** UN1133, ADHESIVE, 3, PGII NMFC# 170060 CLASS 55

**PACKAGING:** 5 gallon reike fitted pails or 1 gallon F-style oblong cans (6 gal/cs)