



NEMEON, Incorporated
6043 Hudson Road Suite 350
Woodbury, MN 55125
www.nemeon.com

TECHNICAL DATA SHEET

SALES NUMBER:	LionGUARD Water Cut-Off Mastic LG-WC30
DESCRIPTION:	Water Cut-Off Mastic is a solvent based caulk designed to seal and protect exposed edges of EPDM membrane from water penetration.
COLOR:	Grey
VISCOSITY (cps):	40# .104= 15-20 sec./20 gms. Sievers Rheometer
DENSITY (#/GAL.):	11.0#
% SOLIDS:	86
FLASH POINT (F):	14 F TCC
BASE:	Synthetic elastomers, resin(s) and filler(s)
SOLVENT SYSTEM:	Aliphatic
CLEAN-UP SOLVENT:	Mineral spirits, VMP naptha, kerosene
STORAGE:	May be stored outside if covered to exclude water.
HAZARDS:	Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire, flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS.
FREIGHT CLASSIFICATION:	UN1133, ADHESIVE, 3, PGII NMFC# 170060 CLASS 55
PACKAGING:	55 gallon drums, 5 gallon pails, 10.5 oz. fiber caulk tubes (10 or 25 tubes/crtn)