

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Section 1. Identification

Product identifier: EPDM Seam Tape Accessories

• Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal

Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Pipe Boot with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape,

Re-Flex TPO Inside/Outside Corners with Tape.

• Relevant identified uses of the substance or mixture: Construction: Sealing Compound

Details of the supplier of the safety data sheet Manufacturer/Supplier

Roofing Products International, Inc.

57460 Dewitt St.

Elkhart, IN 46517-1078 Telephone: 1-574-293-9096

Information Department: Technical Services Department

Emergency telephone number

Chemtrec United States 1(800) 424-9300 International 703-527-3887

Section 2. Hazard(s) Identification

EU/EEC

According to Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010] According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

Classification of the substance or mixture

• CLP Skin Irritation 2 - H315 Skin Sensitization 1 - H317

• **DSD/DPD**Irritant (Xi)

Sensitizer

R38, R43

Label Elements

• CLP

WARNING



Hazard statements H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

Precautionary statements

• **Prevention** P261 - Avoid breathing dust/fume.

P264 - Wash thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace. P280 -Wear protective gloves/protective clothing/eye protection/face protection.

• **Response** P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P321 - Specific treatment, see supplemental first aid information. P362 - Take off contaminated clothing and wash before reuse.

• Storage/Disposal P501 - Dispose of content and/or container in accordance with local, regional,

national, and/or international regulations.

(Contd. on page 2)

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cov

(Contd. of page 1)

DSD/DPD



• Risk phrases R38 - Irritating to skin.

R43 - May cause sensitisation by skin contact.

• Safety phrases S24 - Avoid contact with skin.

S37 - Wear suitable gloves.

S45 - In case of accident or if you feel unwell, seek medical advice

immediately (show the label where possible).

Other Hazards

• *CLP* According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

• DSD/DPD According to European Directive 1999/45/EC this preparation is considered dangerous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

• OSHA HCS 2012 Skin Irritation 2 - H315 Skin Sensitization 1A - H317

Label elements

• OSHA HCS 2012

WARNING



Hazard statements Causes skin irritation - H315

May cause an allergic skin reaction - H317

Precautionary statements

• **Prevention** Avoid breathing dust/fume. - P261

Wash thoroughly after handling. - P264

Contaminated work clothing should not be allowed out of the workplace.- P272 Wear protective gloves/protective clothing/eye protection/face protection.- P280

• Response If skin irritation occurs: Get medical advice/attention. - P332+P313

IF ON SKIN: Wash with plenty of soap and water. - P302+P352

Specific treatment, see supplemental first aid information. - P321

If skin irritation or rash occurs: Get medical advice/attention. - P333+P313

Take off contaminated clothing and wash before reuse. - P362

• Storage/Disposal Dispose of content and/or container in accordance with local, regional, national,

and/or international regulations. - P501

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cov

(Contd. of page 2)

Other hazards

• OSHA HCS 2012

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication

Standard), this product is considered hazardous.

Canada

• According to WHMIS

Classification of the substance or mixture

• WHMIS

Other Toxic Effects - D2B

Label elements

• WHMIS

Other Toxic Effects - D2B



Other hazards

• WHMIS

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

See Section 12 for Ecological Information.

Section 3. Composition/Information on Ingredients

Substances

Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008

| Mixtures | ixtures Composition | | | | |
|---|--|-----------------|--|---|----------|
| Chemical Name | Identifiers | % | LD50/LC50 | Classifications According to Regulation/Directive | Comments |
| Resin | NDA | 4% TO 13% | NDA | EU DSD/DPD: Self Classified: Xi R36/37/38 EU CLP: Self Classified: Eye Irrit. 2A, H319; Skin Irrit. 2, H315; STOT SE 3 - Resp., H335 OSHA HCS 2012: Eye Irrit. 2A; Skin Irrit. 2; STOT SE 3 - Resp. | NDA |
| Talc | CAS:14807-96- 6 EC Number:238- 877-9 | 0% TO 6% | NDA | EU DSD/DPD: Self Classified: Xn R48/20 EU CLP: Self Classified: STOT RE 1, H372 OSHA HCS 2012: STOT RE 1 (Lungs) | NDA |
| Calcium oxide | CAS:1305-78-8 EC Number:215- 138-9 | 1% TO 5% | NDA . | EU DSD/DPD: Self Classified: C R34 EU CLP: Self Classified: Skin Corr. 1C, H314; Eye Dam. 1, H318 OSHA HCS 2012: Skin Corr. 1C; Eye Dam. 1 | NDA . |
| Phenol, p- (1,1,3,3- tetramethylbutyl)- | CAS:140-66-9 EINECS:205- 426-2 | 2% TO 4% | Skin-Rabbit LD50 1880 mg/kg Ingestion/Oral Rat LD50 > 2000 mg/kg | EU DSD/DPD: Annex I: Xi R38-41; N R50-53 EU CLP: Annex VI: Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 OSHA HCS 2012: Eye Irrit. 2A; Skin Irrit. 2; Repr. 2 | NDA |

(Contd. on page 4)

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cov

| (Contd. of page 3) | | | | | |
|---|--|--------------------|--|---|-----|
| Mineral oil, petroleum distillates, hydro- treated (mild) heavy naphthenic | CAS:64742-52- 5 EC Number:265- 155-0 | 0% To 4% | NDA | EU DSD/DPD: Annex I: Carc. 2; R45 EU CLP: Annex VI: Carc. 1B, H350 OSHA HCS 2012: Skin Irrit. 2 | NDA |
| Carbon Black | CAS: 1333-86-4 ECNumber: 215- 609-9 | 1% To 4% | Skin-Rabbit LD50 >3 g/kg Ingestion/Oral-Rat LD50 >15400 mg/kg | EU DSD/DPD: None EU CLP: None OSHA HCS 2012: Carc. 2 | NDA |
| Zinc oxide | CAS: 1314-13-2 EC Number: 215- 222-5 | 0.5% To 2.5% | NDA | EU DSD/DPD: Annex I: N; R50-53 EU CLP: Annex VI: Aquatic Acute 1, H400; Aquatic Chronic 1, H410 OSHA HCS 2012: Eye Irrit. 2B | NDA |
| p-Benzoquinone, 2,3, 5,6-tetrachloro- | CAS: 118-75-2 EC Number: 204-274-4 | 0% To 1.5% | Ingestion/Oral-Rat LD50 • 4 g/kg | EU DSD/DPD: Annex I: Xi R36/38 N R50-53 EU CLP: Annex VI: Eye Irrit. 2, H319; Skin Irrit. 2, H315; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 OSHA HCS 2012: Eye Irrit. 2A; Skin Irrit. 2; STOT RE 3: Resp. Irrit. & Narc.; Acute Tox. 4 (Inhl) | NDA |
| TMDS | CAS: 137-26-8 EC Number: 205-286-2 | 0% To 1% | Ingestion/Oral-Rat LD50 • 560 mg/kg Inhalation-Rat LC50 500 mg/m³ 4 Hour(s) | EU DSD/DPD: Annex I: Xn R20/22 - 48/22 Xi R36/38; R43 N R50-53 EU CLP: Annex VI: Acute Tox. 4, H332; Acute Tox. 4, H302; STOT RE 2, H373; Eye Irrit. 2, H319; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 OSHA HCS 2012: Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1A; Acute Tox. 4 (Oral); Acute Tox. 2 (Inhl) | NDA |
| MBTS | CAS: 120-78-5 EC Number: 204-424-9 | 0% To 1% | Ingestion/Oral-Rat LD50 >12 g/kg Skin-Rabbit LD50 >7940 mg/kg | EU DSD/DPD: Annex I: R31 R43 N; R50-53 EU CLP: Annex VI: Skin Sens. 1, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 OSHA HCS 2012: Skin Sens. 1A | NDA |

Refer to Section 11 for Toxicological Information.

Section 4. First-Aid Measures

- Inhalation First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If signs/symptoms develop, move person to fresh air.

 Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.
- Skin Remove material from skin with waterless hand cleaners followed by washing with soap and water. If signs/symptoms develop, get medical attention.
- Eye First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If contact with material occurs flush eyes with water. If signs/symptoms develop, get medical attention.
- Ingestion First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If signs/symptoms develop, get medical attention.

(Contd. of page 5)

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cov

(Contd. of page 4)

Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

• Note to physician

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5. Fire-Fighting Measures

Extinguishing media

- Suitable Extinguishing Media: Water, foam, dry chemical, carbon dioxide (CO2).
- Unsuitable Extinguishing Media: None known.

Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards: Material releases toxic and corrosive gases/vapors when burned.
- Hazardous Combustion Products: Nitrous oxides, sulfur oxides, carbon oxides.

Advice for firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Structural firefighters' protective clothing will only provide limited protection.

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

• Personal Precautions No special precautions expected to be necessary if material is used

under ordinary conditions as recommended.

• Emergency Procedures

No emergency procedures are expected to be necessary if material is used under ordinary conditions as as recommended. Use normal clean

up procedures.

Environmental precautions

No special precautions necessary.

Methods and material for containment and cleaning up

• Containment/Clean-up Measures:

Pick up pieces and place in container or bag for disposal.

Reference to other sections

Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

* Section 7. Handling and Storage

Precautions for safe handling

Handling

Do not handle at temperatures in excess of 130° F. Avoid prolonged or repeated contact with the skin. Use good safety and industrial hygiene practices. Product readily removed from the skin with waterless hand cleaners followed by washing with soap and water.

(Contd. on page 6)

Revision Date 23/1/2015

Safety Data Sheet acc. to OSHAHCS

Article Number 104 Revision Number 2

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cover

(Contd. of page 5)

Conditions for safe storage, including any incompatibilities

• Storage

Store in a cool, dry place. Do not store at temperatures in excess of 130° F.

• Specific end uses

Refer to Section 1.2 - Relevant identified uses.

Section 8. Exposure Controls/Personal Protection

| Exposure Limits/Guidelines | | | | | | | | |
|--------------------------------------|----------|---|--|--|---|---|--|--|
| | Result | ACGIH | Belgium | Canada Alberta | Canada British Columbia | Canada Manitoba | | |
| Formaldehyde (50-00-0) | Ceilings | 0.3 ppm Ceiling | Not Established | 1 ppm Ceiling; 1.3 mg/m3 Ceiling | 1 ppm Ceiling | 0.3 ppm Ceiling | | |
| | TWAs | Not Established | Not Established | 2@7'rro 'VY C= '20 'o i lo 5'VY C | 0.3 ppm TWA | Not established | | |
| TMDS *359/48/: + | TWAs | 2@7" o i lo 5" VY C' *kpj credrg" lt cevkqp' cpf "xcrqt+ | ' 2027'o i lo 5'VY C" ' *egtquqrl'epf 'xerqt +=" 2027'rro 'VY C" *egtquqrl'epf 'xerqt + | 3"o i lo 5"VY C | 3"o i lo 5"VY C | 2@7"o i lo 5"VY C" *kpj crcdrg'ht ceskqp cpf 'xcrqt+ | | |
| Talc *36: 29/; 8/8+ | TWAs | 2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction) | 2 mg/m3 TWA | 2 mg/m3 TWA *1 gur kt cdng particulate)" | 2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction) | 2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction) | | |
| 3/Rt qr gpg."4/ methyl-*337/33/9+ | TWAs | 472"rro "VY C"*hungf" wpf gt "Dwgpgu"cm! huqo gtu+ | 472"rro "VY C=" 7: 5"o i lo 5"VY C | Not Established | Not Established | 472"rro "VY C *hug wpf gt Dwypgu "cm" huqo gt u+ | | |
| ENB (16219-75-3) | Ceilings | 5 ppm Ceiling | Not Established | 5 ppm Ceiling; 25 mg/m | 5 ppm ceiling | 5 ppm Ceiling | | |
| Sulfur (7704-34-9) | TWAs | Not established | Not established | 10 mg/m3 TWA | Not established | Not established | | |
| Zinc oxide (1314-13-2) | STELs | 10 mg/m3 STEL (respirable fraction) | 10 mg/m3 STEL (fume) | 10 mg/m3 STEL (respirable) | 10 mg/m3 STEL (respirable) | 10 mg/m3 STEL (respirable fraction) | | |
| | TWAs | 2 mg/m3 TWA (respirable fraction) | 0 mg/m3 TWA (dust); 5 mg/m3 TWA (fume) | 2 mg/m3 TWA (respirable) | 2 mg/m3 TWA (respirable) | 2 mg/m3 TWA (respirable fraction | | |
| Carbon Black (1333-86-4) | TWAs | 3 mg/m3 TWA (inhalable fraction) | 3.5 mg/m3 TWA | 3.5 mg/m3 TWA | 3 mg/m3 TWA (inhalable) | 3 mg/m3 TWA (inhalable fraction) | | |
| | | Ex | posure Limits/Gui | delines Continued | ! | | | |
| Formaldehyde | Result | Canada New Brunswick | Canada Nunavut | Canada Nova Scotia | Canada Northwest Territories | Canada Ontario | | |
| (50-00-0) | STELs | 1.5 ppm STEL | Not established | Not established | Not established | 1.0 ppm STEL | | |
| | TWAs | 0.5 ppm TWA | Not established | Not established | Not established | Not established | | |
| | Ceilings | Not established | 2 ppm Ceiling; 2.4 mg/m3 Ceiling | 0.3 ppm Ceiling | 2 ppm Ceiling; 2.4 mg/m3 Ceiling | 1.5 ppm Ceiling | | |

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cover

| | | | (Contd. of p | page 6) | | |
|--|----------|---|---|--|---|--|
| TMDS (137-26-8) | TWAs | 1 mg/m3 TWA | 5 mg/m3 TWA | 0.05 mg/m3 TWA (inhalable fraction and vapor) | | 0.05 mg/m3 TWA (inhalable fractio and vapor, listed under Thiram) |
| | STELs | Not established | 10 mg/m3 STEL | Not established | 10 mg/m3 STEL | Not established |
| Talc (14807-96-6) | TWAs | 2 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction) | 3 mg/m3 TWA (respirable mass); 6 mg/m3 TWA (total mass) | 2 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction | 6 mg/m3 TWA (total mass) | 2 mg/m3 TWA (containing no Asbestos and <1% Crystalline silica, respirable |
| 1-Propene, 2- methyl- (115-11-7) | TWAs | Not established | Not established | 250 ppm TWA (liste under Butenes, all isomers) | ed Not established | 250 ppm TWA (listed under Butenes, all isomers) |
| ENB (16219-75-3) | Ceilings | 5 ppm Ceiling; 25 mg/m3 Ceiling | 5 ppm Ceiling; 25 mg/m3 Ceiling | 5 ppm Ceiling | 5 ppm Ceiling; 25 mg/m3 Ceiling | 5 ppm Ceiling |
| Zinc oxide ·(1314-13-2) | STELs | 10 mg/m3 STEL (fume) | 10 mg/m3 STEL (fume) | 10 mg/m3 STEL (respirable fraction | 10 mg/m3 STEL n) (fume) | 10 mg/m3 STEL (respirable) |
| | TWAs | 10 mg/m3 TWA (particulate matter containing no Asbestos and <1% Crystalline silica, dust); 5 mg/ m3 TWA (fume) | 5 mg/m3 TWA (fume); 5 mg/m3 TWA (dust, res- pirable mass); 10 mg/m3 TWA (total mass, dust) | 2 mg/m3 TWA (respirable fraction | 5 mg/m3 TWA (fume); 5 mg/m3 TWA (dust, respirable mass); 10 mg/m3 TW (total mass, dust) | |
| Carbon Black (1333-86-4) | TWAs | 3.5 mg/m3 TWA | 3.5 mg/m3 TWA | 3 mg/m3 TWA (inhalable fraction, | 3.5 mg/m3 TWA | 3.5 mg/m3 TWA |
| | STELs | Not established | 7 mg/m3 STEL | Not established | 7 mg/m3 STEL | Not established |
| | | Expe | osure Limits/Guid | lelines Continued | | |
| | Result | Canada Quebec | Canada Saskatchewan | Canada Yukon | NIOSH | OSHA |
| | STELs | Not established | Not established | Not established | | 2 ppm STEL (see 29 CFR 1910.1048) |
| Formaldehyde (50-00-0) | Ceilings | 2 ppm Ceiling; 3 mg/m3 Ceiling | Not established | 2 ppm Ceiling; 3 mg/m3 Ceiling | 0.1 ppm Ceiling (15 min) | Not established |
| | TWAs | Not established | Not established | Not established | 0.016 ppm TWA | 0.75 ppm TWA |
| | TWAs | 5 mg/m3 TWAEV | 1 mg/m3 TWA | 5 mg/m3 TWA | 5 mg/m3 TWA | 5 mg/m3 TWA |
| TMDS | STELs | Not established | Not established | 10 mg/m3 STEL | Not established | Not established |
| (137-26-8) | Ceiling | Not established | Not established | Not established | Not established | Not established |
| | MAKs | Not established | Not established | Not established | Not established | Not established |
| Talc (14807-96-6) | TWAs | 3 mg/m3 TWAEV (respirable dust) | 2 mg/m3 TWA (respirable fraction) | 20 mppcf TWA | 2 mg/m3 TWA (containing no Asbestos and <1% Quartz, respirable dust) | Not established |
| Isoprene | Ceilings | Not established | Not established | Not established | Not established | Not established |
| (78-79-5) | MAKs | Not established | Not established | Not established | Not established | Not established |
| ENB (16219-75-3) | Ceilings | 5 ppm Ceiling; 25 mg/m3 Ceiling | Not established | 5 ppm Ceiling; 25 mg/m3 Ceiling | 5 ppm Ceiling; 25 mg/m3 Ceiling | Not established |

Article Number 104

Revision Number 2

Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cov

| | (Contd. of page 7) | | | | | | | |
|--|-----------------------------|----------|---|--|---|--|--|--|
| | | TWAs | 10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust); 5 mg/m3 TWAEV (fume) | 2 mg/m3 TWA (dust and fume, respirable fraction) | 5 mg/m3 TWA (fume); 30 mppcf TWA (dust); 10 mg/m3 TWA (dust) | 5 mg/m3TWA dust and fume) | 5 mg/m TWA (fume); 15 mg/m TWA total dust)5 mg/m TWA (respirable fraction) | |
| | Zinc oxide (1314-13-2) | STELs | 10 mg/m3 STEV (fume) | Not established | 10 mg/m3 STEL (fume); 20 mg/m3 STEL (dust) | 10 mg/m3 STEL (fume) | Not established | |
| | | Ceilings | Not established | Not established | Not established | 15 mg/m Ceiling dust) | Not established | |
| | | MAKs | Not established | Not established | Not established | Not established | 1 mg/m3 TWA MAK (fume, respirable fraction) | |
| | Carbon Black (1333-86-4) | TWAs | 3.5 mg/m3 TWAEV | 3.5 mg/m3 TWA | 3.5 mg/m3 TWA | 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon | 3.5 mg/m3 TWA | |
| | | | Not established | Not established | 7 mg/m3 STEL | black in presence of Polycyclic aromatic hydrocarbons, as PAH) | | |

Exposure controls

• Engineering Measures/Controls

Under normal conditions of use, special ventilation is not required.

• Personal Protective Equipment

• Respiratory

No respiratory protection is required under normal conditions of use.

• Eye/Face

Under normal conditions of use, eye protection is not required.

• Skin/Body

Wear appropriate gloves.

Follow best practice for site cleanup and disposal of waste.

Environmental Exposure Controls

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

 $NIOSH = National\ Institute\ of\ Occupational\ Safety\ and\ Health$

 $OSHA = Occupational \ Safety \ and \ Health \ Administration$

STEL = Short Term Exposure Limits are based on 15-minute exposures

STEV = Short Term Exposure Value

TWAEV = Time-Weighted Average Exposure Value Time-Weighted Averages are based on 8h/day, 40h/

week TWA exposures

Section 9. Physical and Chemical Properties

Information on Physical and Chemical Properties

| Material Description | | | | | |
|----------------------|-------|------------------------|--|--|--|
| Physical Form | Solid | Appearance/Description | Black solid (EPDM) laminated to tape. No odor. | | |
| Color | Black | Odor | None | | |
| Odor Threshold | None | | | | |

(Contd. on page 9)

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cov

| | (Con | ntd. of page 8) | |
|-------------------------------------|------------------|----------------------|--------------------|
| | Gener | al Properties | |
| Boiling Point | Not relevant | Melting Point | Data lacking |
| Decomposition Temperature | Data lacking | pН | Not relevant |
| Specific Gravity/Relative Density | 0.97 Water=1 | Water Solubility | Negligible < 0.1 % |
| Viscosity | Not relevant | Explosive Properties | Not relevant. |
| Oxidizing Properties | Not relevant. | | |
| | V | <i>Solatility</i> | |
| Vapor Pressure | Not relevant | Vapor Density | Not relevant |
| Evaporation Rate | Not relevant | Volatiles (Vol.) | 0.7 % |
| | Fla | ımmability | |
| Flash Point | > 200 C(> 392 F) | UEL | Not relevant |
| LEL | Not relevant | Autoignition | Not relevant |
| Flammability (solid, gas) | Not flammable. | | |
| | Env | rironmental | |
| Octanol/Water Partition coefficient | Data lacking | | |

Other Information

No additional physical and chemical parameters noted.

Section 10. Stability and Reactivity

Reactivity

• Chemical stability

No dangerous reaction known under conditions of normal use.

• Possibility of hazardous reactions

Stable under normal temperatures and pressures. Hazardous polymerization will not occur.

• Conditions to avoid

Temperatures in excess of 130° F.

• Incompatible materials

No data available.

• Hazardous decomposition products

Thermal decomposition could produce CO, CO2, and Oxides of Nitrogen.

Section 11. Toxicological Information

| Component Name | CAS | Data |
|---|------------|---|
| Phenol, p-(1,1,3,3-tetramethylbutyl)- (2% TO 4%) | 140-66-9 | Acute Toxicity: orl-rat LD50:4600 mg/kg; skn-rbt LD50:1880 mg/kg; Irritation: eye-rbt 50 ug/24H SEV; skn-rbt 20 mg/24H MOD; Reproductive: orl-mus TDLo:2.4 mg/kg (10-21D preg/12D post); orl-mus TDLo:14000 ng/kg (11-17D preg); orl-rat TDLo:250.4 mg/kg (0-8D preg) |
| Mineral oil, petroleum distillates, hydrotreated (mild) heavy naphthenic (0% TO 4%) | 64742-52-5 | Irritation: skn-rbt 500 mg SEV |
| Carbon Black (1% TO 4%) | 1333-86-4 | Acute Toxicity: orl-rat LD50:>15400 mg/kg; skn-rbt LD50:>3 gm/kg; Tumorigen/Carcinogen: ihl-rat TCLo:11600 ug/m3/18H/2Y-1 |

(Contd. on page 10)

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cov

| | (Con | td. of page 9) | | |
|---|-----------|---|--|--|
| Component Name | CAS | Data | | |
| Talc (0% TO 6%) 14807-96-6 | | Irritation: skn-hmn 300 ug/3D-I MLD; Tumorigen/ Carcinogen: ihl-rat TC:11 mg/m3/1Y-I | | |
| Zinc oxide (0.5% TO 2.5%) | 1314-13-2 | Irritation: eye-rbt 500 mg/24H MLD; skn-rbt 500 mg/24H MLD; Reproductive: orl-rat TDLo:6846 mg/kg (1-22D preg) | | |
| MBTS (0% TO 1%) | 120-78-5 | Acute Toxicity: orl-rat LD50:>12 gm/kg; skn-rbt LD50:>7940 mg. | | |
| p-Benzoquinone, 2,3,5,6-tetrachloro- (0% TO 1.5%) | 118-75-2 | Acute Toxicity: orl-rat LD50:4 gm/kg; ihl-rat LC50:2485 mg/m3/4 | | |
| TMDS (0% TO 1%) 137-26-8 | | Acute Toxicity: Ingestion/Oral-Rat LD50 • 560 mg/kg; ihl-rat LC50 500mg/m3/4H; Irritation: eye-rbt 100 mg/24H MOD; Reproductive: orl-rat TDLo:300 mg/kg (15D preg); Tumorigen/Carcinogen: orl-rat TDLo:108 mg/kg/1Y-C | | |
| GHS Properties | | Classification | | |
| Acute toxicity | | EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met | | |
| Aspiration Hazard | | EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met | | |
| Carcinogenicity | | EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met | | |
| Germ Cell Mutagenicity | | EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met | | |
| Skin corrosion/Irritation | | EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2 | | |
| Skin sensitization | | EU/CLP • Skin Sensitizer 1 OSHA HCS 2012 • Skin Sensitizer 1A | | |
| STOT-RE | | EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met | | |
| STOT-SE | | EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met | | |
| Toxicity for Reproduction | | EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met | | |
| Respiratory sensitization | | EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met | | |
| Serious eye damage/Irritation | | EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met | | |

Potential Health Effects Inhalation

| • Acute (Immediate) | Under normal conditions of use, no health effects are expected. |
|---------------------------------------|---|
| Chronic (Delayed) | Under normal conditions of use, no health effects are expected. |
| Skin | |

Acute (Immediate)
 Chronic (Delayed)

Causes skin irritation. May cause an allergic skin reaction. Under

OSHA HCS 2012 • Classification criteria not met

• Chronic (Delayed) normal conditions of use, no health effects are expected.

Eye

Acute (Immediate) Direct contact with tape may cause mechanical irritation.
 Chronic (Delayed) Under normal conditions of use, no health effects are expected.

(Contd. on page 11)

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Pipe Boot with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape

(Contd. of page 10)

Ingestion

• Acute (Immediate) Under normal conditions of use, no health effects are expected. • Chronic (Delayed) Under normal conditions of use, no health effects are expected.

Carcinogenic Effects

Although this material does contain several components that are either carcinogens or potential carcinogens the material as a whole is not classified as a carcinogen according to regulatory guidelines. The carbon black is encapsulated within the matrix of this material and no exposure is expected. The isoprene and formaldehyde components are both in this material at low enough concentrations that this material is not classified as a carcinogen per agency guidelines.

| Carcinogenic Effects | | | | | | |
|----------------------|-----------|-----------------------------------|------------------------------|---|--|--|
| | CAS | OSHA | IARC | NTP | | |
| Formaldehyde | 50-00-0 | Specifically Regulated Carcinogen | Group 1-Carcinogenic | Known Human Carcinogen | | |
| Isoprene | 78-79-5 | Not Listed | Group 2B-Possible Carcinogen | Reasonably Anticipated to be Human Carcinogen | | |
| Carbon Black | 1333-86-4 | Not Listed | Group 2B-Possible Carcinogen | Not Listed | | |
| Key to abbreviate | ions | SEV = Severe | • | • | | |

= Lethal Concentration LC

TC = Toxic Concentration

= Lethal Dose

 $TD = Toxic\ Dose$

MLD = Mild

MOD = Moderate

Section 12. Ecological Information

Toxicity

- Aquatic toxicity: No further relevant information available.
- **Persistence and degradability:** No further relevant information available.

Behavior in environmental systems

- Bioaccumulative potential: No further relevant information available.
- *Mobility in soil:* No further relevant information available.

Ecotoxical effects

• **Remark:** No further relevent information available.

Additional ecological information

General notes: At present there are no ecotoxicological assessments.

Results of PBT and vPvB

- assessment PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

Section 13. Disposal Considerations

Waste treatment methods

- Product waste handling
- **Recommendation:** Dispose of waste product and/or container according to local, regional, state, and national/
- international regulations.
- Packaging waste handling
- **Recommendation:** Dispose of packaging or container according to local, regional, state, and national/ international regulations.

(Contd. on page 12)

Article Number 104 Revision Number 2

Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cover

(Contd. of page 11)

* Section 14. Transport Information

| | UN number | UN proper shipping name | Transport hazard class(es) | Packing group | Environmental hazards |
|-----------|--------------|----------------------------|----------------------------|------------------|--------------------------|
| DOT | NDA | Not Regulated | NDA | NDA | NDA |
| TDG | NDA | Not Regulated | NDA | NDA | NDA |
| IMO/IMDG | NDA | Not Regulated | NDA | NDA | NDA |
| ADN | NDA | Not Regulated | NDA | NDA | NDA |
| ADR/RID | NDA | Not Regulated | NDA | NDA | NDA |
| IATA/ICAO | NDA | Not Regulated | NDA | NDA | NDA |

- Special precautions for user None known.
- Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not Relevent.

Section 15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications Acute

| Component | CAS | MA | NJ | P A |
|---|------------|-----|-----|------------|
| 1-Propene, 2-methyl- | 115-11-7 | Yes | Yes | Yes |
| ENB | 16219-75-3 | Yes | Yes | Yes |
| MBTS | 120-78-5 | No | No | No |
| Calcium oxide | 1305-78-8 | Yes | Yes | Yes |
| Carbon Black | 1333-86-4 | Yes | Yes | Yes |
| TMDS | 137-26-8 | Yes | Yes | Yes |
| Ethylene propylene diene rubber | 25038-36-2 | No | No | No |
| Formaldehyde | 50-00-0 | Yes | Yes | Yes |
| Mineral oil, petroleum distillates, hydrotreated (mild) heavy naphthenic | 64742-52-5 | No | No | No |
| Isobutylene-Isoprene polymer | 9010-85-9 | No | No | No |
| Isoprene | 78-79-5 | Yes | Yes | Yes |
| p-Benzoquinone, 2,3,5,6-tetrachloro- | 118-75-2 | No | No | No |
| Phenol, 4-methyl | 68610-51-5 | No | No | No |
| Phenol, p-(1,1,3,3-tetramethylbutyl)- | 140-66-9 | No | No | No |
| Polybutene | 9003-29-6 | No | No | No |
| Sulfur | 7704-34-9 | Yes | Yes | Yes |
| Talc | 14807-96-6 | Yes | Yes | Yes |
| Zinc oxide | 1314-13-2 | Yes | Yes | Yes |

(Contd. on page 13)

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Re-Flex Cover Tape Re-Flex Uncured Flashing with Tape Re-Flex Seam Tape Re-Flex TPO Cover Tape Re-Fle

| | | (Contd. of page 1 | 2) | | |
|--|------------------------|-------------------|-------------|--|--|
| Inventory | | | | | |
| Component | CAS | Canada DSL | Canada NDSL | | |
| 1-Propene, 2-methyl- | 115-11-7 | Yes | No | | |
| ENB | 16219-75-3 | No | Yes | | |
| MBTS | 120-78-5 | Yes | No | | |
| Calcium oxide | 1305-78-8 | Yes | No | | |
| Carbon Black | 1333-86-4 | Yes | No | | |
| TMDS | 137-26-8 | Yes | No | | |
| Ethylene propylene diene rubber | 25038-36-2 | Yes | No | | |
| Formaldehyde | 50-00-0 | Yes | No | | |
| Mineral oil, petroleum distillates, hydrotreated (mild) heavy naphthenic | 64742-52-5 | Yes | No | | |
| Isobutylene-Isoprene polymer | 9010-85-9 | Yes | No | | |
| Isoprene | 78-79-5 | Yes | No | | |
| p-Benzoquinone, 2,3,5,6-tetrachloro- | 118-75-2 | Yes | No | | |
| Phenol, 4-methyl | 68610-51-5 | Yes | No | | |
| Phenol, p-(1,1,3,3-tetramethylbutyl)- | 140-66-9 | Yes | No | | |
| Polybutene | 9003-29-6 | Yes | No | | |
| Sulfur | 7704-34-9 | Yes | No | | |
| Talc | 14807-96-6 | Yes | No | | |
| Zinc oxide | 1314-13-2 | Yes | No | | |
| Canada Labor Canada - WHMIS - Classifice • Phenol, 4-methyl | ations of Subs | tances | | Not Listed | |
| • Isobutylene-Isoprene polymer | 9010-85-9 | | | Not Listed | |
| • Isoprene | 78-79-5 | | | Not Listed | |
| • 1-Propene, 2-methyl- | 115-11-7 | | | Not Listed | |
| MBTS Ethylene propylene diene rubber | 120-78-5 25038-36-2 | | | Not Listed Not Listed | |
| • TMDS | 137-26-8 | | | Not Listed | |
| Formaldehyde | 50-00-0 | | | Not Listed A, B1, D1A, D2A, D2B; B3, 1A, D2A, D2B, E (regulated under Formol) | |
| • Calcium oxide | 1305-78-8 | | | E | |
| Carbon Black | 1333-86-4 | | | D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues -Carbon Black, non- | |

(Contd. on page 14)

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Corners with Tape.

| | (Contd. of page 13) | |
|---|---------------------|---|
| Talc | 14807-96-6 | D2A |
| Zinc oxide | 1314-13-2 | Uncontrolled product according to WHMIS classification criteri |
| Zinc oxide as Zinc compounds | | Not Listed |
| Polybutene | 9003-29-6 | Uncontrolled product according to WHMIS classification criteria |
| Sulfur | 7704-34-9 | B4 |
| ENB | 16219-75-3 | B2, D1A, D2B |
| p-Benzoquinone, 2,3,5,6-tetrachloro- | 118-75-2 | Not Listed |
| Phenol, p-(1,1,3,3-tetramethylbutyl)- | 140-66-9 | Uncontrolled product according to WHMIS classification criteria |
| Mineral oil, petroleum distillates, hydrotreated (mild) heavy naphthenic | 64742-52-5 | Not Listed |
| Canada WHMIS - Ingredient Disclosure I | List | |
| Phenol, 4-methyl | 68610-51-5 | Not Listed |
| Isobutylene-Isoprene polymer | 9010-85-9 | Not Listed |
| Isoprene | 78-79-5 | 1 % |
| 1-Propene, 2-methyl- | 115-11-7 | Not Listed |
| MBTS | 120-78-5 | 1 % |
| Ethylene propylene diene rubber | 25038-36-2 | Not Listed |
| TMDS | 137-26-8 | 1 % |
| Formaldehyde | 50-00-0 | 0.1 % |
| Calcium oxide | 1305-78-8 | 1 % |
| Carbon Black | 1333-86-4 | 1 % |
| Talc | 14807-96-6 | Not Listed |
| Zinc oxide | 1314-13-2 | 1 % |
| Zinc oxide as Zinc compounds | | Not Listed |
| Polybutene | 9003-29-6 | Not Listed |
| Sulfur | 7704-34-9 | Not Listed |
| ENB | 16219-75-3 | 1 % |
| p-Benzoquinone, 2,3,5,6-tetrachloro- | 118-75-2 | Not Listed |
| Phenol, p-(1,1,3,3-tetramethylbutyl)- | 140-66-9 | Not Listed |
| Mineral oil, petroleum distillates, hydrotreated (mild) heavy naphthenic | 64742-52-5 | Not Listed |
| Environment Canada - CEPA - Priority Substan | ces List | |
| Phenol, 4-methyl | 68610-51-5 | Not Listed |
| Isobutylene-Isoprene polymer | 9010-85-9 | Not Listed |
| Isoprene | 78-79-5 | Not Listed |
| 1-Propene, 2-methyl- | 115-11-7 | Not Listed |
| MBTS | 120-78-5 | Not Listed |
| Ethylene propylene diene rubber | 25038-36-2 | Not Listed |
| TMDS | 137-26-8 | Not Listed |
| Formaldehyde | 50-00-0 | Priortiy Substance List 2 (substance considered toxic) |

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cover

| (Contd. of page 14) | | |
|--|------------|---|
| Calcium oxide | 1305-78-8 | Not Listed |
| Carbon Black | 1333-86-4 | Not Listed |
| Talc | 14807-96-6 | Not Listed |
| Zinc oxide | 1314-13-2 | Not Listed |
| Zinc oxide as Zinc compounds | | Not Listed |
| Polybutene | 9003-29-6 | Not Listed |
| Sulfur | 7704-34-9 | Not Listed |
| ENB | 16219-75-3 | Not Listed |
| p-Benzoquinone, 2,3,5,6-tetrachloro- | 118-75-2 | Not Listed |
| Phenol, p-(1,1,3,3-tetramethylbutyl)- | | Not Listed |
| | 140-66-9 | |
| Mineral oil, petroleum distillates, hydrotreated (mild) heavy naphthenic | 64742-52-5 | Not Listed |
| United States Labor U.S OSHA - Process Safety Management - Highly Hazardous Chemicals | | |
| • Phenol, 4-methyl | 68610-51-5 | Not Listed |
| • Isobutylene-Isoprene polymer | 9010-85-9 | Not Listed |
| • Isoprene | 78-79-5 | Not Listed |
| • 1-Propene, 2-methyl- | 115-11-7 | Not Listed |
| • MBTS | 120-78-5 | Not Listed |
| Ethylene propylene diene rubber | 25038-36-2 | Not Listed |
| TMDS | 137-26-8 | Not Listed |
| Formaldehyde | 50-00-0 | 1000 lb TQ |
| • Calcium oxide | 1305-78-8 | Not Listed |
| • Carbon Black | 1333-86-4 | Not Listed |
| • Talc | 14807-96-6 | Not Listed |
| • Zine oxide | 1314-13-2 | Not Listed |
| • Zinc oxide as Zinc compounds | | Not Listed |
| • Polybutene | 9003-29-6 | Not Listed |
| • Sulfur | 7704-34-9 | Not Listed |
| • ENB | 16219-75-3 | Not Listed |
| • p-Benzoquinone, 2,3,5,6-tetrachloro- | 118-75-2 | Not Listed |
| • Phenol, p-(1,1,3,3-tetramethylbutyl)- | 140-66-9 | Not Listed |
| Mineral oil, petroleum distillates, hydrotreated (mild) heavy naphthenic | 64742-52-5 | Not Listed |
| U.S OSHA - Specifically Regulated Chemicals | | |
| Phenol, 4-methyl | 68610-51-5 | Not Listed |
| Isobutylene-Isoprene polymer | 9010-85-9 | Not Listed |
| Isoprene | 78-79-5 | Not Listed |
| 1-Propene, 2-methyl- | 115-11-7 | Not Listed |
| • MBTS | 120-78-5 | Not Listed |
| • Ethylene propylene diene rubber | 25038-36-2 | Not Listed |
| TMDS | 137-26-8 | Not Listed |
| r Formaldehyde | 50-00-0 | 2 ppm STEL (Irritant and potential cance hazard, See 29 CFR 1910.104 15 min); 0.5 pp |
| (Contd. on page 16) | | Action Level; 0.75 ppm TWA |

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cov

| (Contd. of page 15) | | |
|---|-------------------------|------------------------|
| Calcium oxide | 1305-78-8 | Not Listed |
| Carbon Black | 1333-86-4 | Not Listed |
| • Talc | 14807-96-6 | Not Listed |
| • Zinc oxide | 1314-13-2 | Not Listed |
| Zinc oxide as Zinc compounds | | Not Listed |
| • Polybutene | 9003-29-6 | Not Listed |
| • Sulfur | 7704-34-9 | Not Listed |
| • ENB | 16219-75-3 | Not Listed |
| • p-Benzoquinone, 2,3,5,6-tetrachloro- | 118-75-2 | Not Listed |
| • Phenol, p-(1,1,3,3-tetramethylbutyl)- | 140-66-9 | Not Listed |
| Mineral oil, petroleum distillates, hydrotreated (mild) heavy naphthenic | 64742-52-5 | Not Listed |
| Phenol, 4-methyl Isobutylene-Isoprene polymer | 68610-51-5 9010-85-9 | Not Listed Not Listed |
| Environment U.S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants | | |
| Isobutylene-Isoprene polymer | 9010-85-9 | Not Listed |
| • Isoprene | 78-79-5 | Not Listed |
| • 1-Propene, 2-methyl- | 115-11-7 | Not Listed |
| • MBTS | 120-78-5 | Not Listed |
| Ethylene propylene diene rubber | 25038-36-2 | Not Listed |
| • TMDS | 137-26-8 | Not Listed |
| U.S California - Proposition 65 - Carcinogens List: Not Listed U.S California - Proposition 65 - Developmental Toxicity: Not Li | isted | |
| U.S California - Proposition 65 - Maximum Allowable Dose Lev | | |
| U.S California - Proposition 65 - No Significant Risk Levels (NSI | | |
| U.S California - Proposition 65 - Reproductive Toxicity - Female | | |
| U.S California - Proposition 65 - Reproductive Toxicity - Male: | | |
| | Ivoi Lisieu | |
| United States - Pennsylvania | | |
| Labor | | |
| Lubbi | | |
| U.S Pennsylvania - RTK (Right to Know) - Environmental Hazar | rd List: Not Listed | |

Chemical Safety Assessment: Chemical Safety Assessment is not required.

Section 16. Other Information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Roofing Products International, Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Roofing Products International, Inc. or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- Department issuing SDS: Technical Services Department.
- Creation Date: 08/12/2000
- Date of preparation/last revision 03/21/2007

(Contd. on page 17)

Article Number 104 Revision Number 2 Revision Date 23/1/2015

Trade name: Royal Edge Seam Tape, Royal Edge Cover Tape, Royal Edge Uncured Flashing with Tape, Royal Edge Pipe Boot with Tape, Royal Edge RPS with Tape, Re-Flex Cover Tape, Re-Flex Uncured Flashing with Tape, Re-Flex Seam Tape, Re-Flex TPO Cover Tape, Re-Flex TPO Cov

(Contd. of page 16)

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

End of SDS