

## ROYAL EDGE TERMINATION BAR TECHNICAL DATA SHEET

### PRODUCT DATA

PROPERTY	MINIMUM PERFORMANCE
Corrosion Resistance:	Meets FM 4470 criteria
Material:	Aluminum
Length:	10 ft. pieces
Width:	1.0 inch
Thickness:	.0448" - .0510"
Holes:	6 inches O.C.



### DESCRIPTION:

RPI Termination Bar is a high strength, aluminum bar with installation holes 6 inches on center. Termination Bar is used when terminating Royal Edge EPDM, Re-Flex EPDM, and Re-Flex TPO to walls, fascia, and other details which require a mechanical termination of the membrane. Use approved fasteners that are appropriate for specific substrates.

### APPLICATION INSTRUCTIONS:

#### Installation of RPI Termination Bar:

1. After the membrane is installed, place the termination bar over the membrane and secure to the substrate. Use Water Cut-Off and Lap Caulk where required, (see installation specification manual). To minimize bowing, RPI Termination Bar should be secured starting at one end of the bar, installing to the other end; or beginning in the middle and installing towards both ends. Do not overlap the bar. Leave a minimum 1/8 inch space between bars for expansion. Use only approved fasteners that are appropriate for specific substrates.

**Refer to the RPI Specification Manual for complete installation details.**

### PACKAGING:

50 - 10 ft. pieces per carboard tube

### RECOMMENDED STORAGE:

Store in dry area, protected from weather.

### PRECAUTIONARY DATA:

1. Do not overlap Termination Bar.
2. Check for sharp edges or burs on bar. If found, remove before installing.
3. Termination Bar should be stored in original carboard shipping containers.

Information stated on this Roofing Products International, Inc. Data Sheet is intended to provide basic guidance as to storage, application, coverage, shipping, and other product data. Information is subject to change without notice. For more information regarding this product, refer to RPI MSDS, and the RPI Specification Manual. As neither Roofing Products International, Inc. nor its representatives practice structural engineering or architecture, RPI disclaims any responsibility and offers no opinion as to the structural soundness of any structure on which its products may be applied. The building owner should obtain the services of a competent structural engineer before proceeding. RPI accepts no responsibility for any structural failure or resultant damages. No Roofing Products International, Inc. representative is authorized to vary this disclaimer.