

10" Model

Common applications: Bathrooms, Hallways, Entry Ways, Closets, Small Kitchens, Bedrooms, Laundry Rooms, Small Workspaces, and Hobby Rooms



Light Output:

Illuminates up to 150 sq. ft. Equivalent of up to 300 watts Max. light pipe length = 18 feet

Performance Features:

25-Year Product Warranty Hurricane Tested/Approved ICC-ES Listed

Flashing Types:

Curb Mount Flat Roof

Flashing Colors: Mill Finish Aluminum

Diffuser Styles: Prismatic (Flat or Curved) Soft White (Flat or Curved)

Accessories Available:

Electric Light Kit Dimmer Kit Additional Light Pipe Angle Adapter (Elbow)



10" Specifications



Dome Assembly Clear UV Protected, 100% High Impact Modified - Secured with 1/4" Sheet Metal Screws	6" 1" ÷ • • • • • • • • • •
Flashing Housing Commercial Pure Grade Aluminum 5 Choice of Curb Mount or Flat Roof Secured with 1 1/2" Screws Insulated with Horsehair Gasket	4.25" ↓ 1.5" ↓
• Light Pipe (2) Sections of 24" super reflective Miro Silver" interior - Secured with Tek Screws and Aluminum Foil Tape	24" < 10">
Ceiling Ring Secured with 1 1/2" Screws and Speed Nuts Insulated with Horsehair Gasket	
Trim with Diffuser Powder Coated white Trim Ring with the choice of Prismatic (standard) or Soft White Diffuser. Both Diffusers available in Curved or Flat	

Flat Roof Flashing

