# **PRODUCT SPECIFICATIONS** PCV-1 POWERED CRAWLSPACE VENT

### 1.1 MATERIALS:

#### **1.1.1 Plastic Polymers:** Mounting Plate: 0.125" Filled polypropylene with UV stabilization additives.

# **1.1.2 Galvanized Steel:** Electrical Control Box: 0.036" Galvanized Steel Coiled Sheet.

## 1.2 MISCELLANEOUS:

- **1.2.1 Description:** Powered foundation vent for providing fresh air ventilation to a crawl space. Designed to mount behind existing 8" x 16" foundation vent. Three prong, grounded plug for safety and convenience. UL listed and CSA certified.
- **1.2.2** Color: Available in BLACK finish.
- **1.2.3** Fan: 110 CFM electric case fan.
- **1.2.4** Thermostat/Humidistat: Preset thermostat turns off at 40°F and on at 50°F or higher. The humidistat is preset to 60% RH and is adjustable from 20% RH to 80% RH. Includes thermal protection for safety.
- **1.2.5** Dimensions: 9"" x 19" x 3"
- **1.2.5 Packaging:** Packaged 6 to a carton. UPC labels are attached to each vent and carton.



P.O. Box 519 Jacksonville, AR 72078 1-800-643-5596 phone 501-982-1258 fax